

VALEN BATTERY CHARGER

BC VCC2404

- The Valen 24V 4A Convection Cooled Charger boasts superior quality and reliability, with the ability to correctly charge and maintain mobility batteries ensuring longevity.
- The Valen 24V 4A has an input voltage of 110V to 240V, allowing it to operate universally.
- Thermal protection against overheating is built-in, as well as reverse polarity, output shorting and spark protection.





BC VCC2404

BATTERY CHARGER

SPECIFICATIONS

Innovative Features

- Convection Cooling = no fan, no noise!
- Handle on the charger ensures it's easily portable
- Canon/XLR plug for mobility scooters and power wheelchair applications

LED Indication

- Yellow on: Battery charging capacity
- Green on: Fully charged
- Orange Flash: Charger self-test fail
- Orange on: Charger not connected to the battery
- Orange & Yellow on: Normal charging
- Red Flash: Battery connected in the wrong polarity
- Red on: Low battery voltage/Wrong Battery

Specifications

Input Voltage	100 - 240VAC
Output Current	4A
Cooling	Convection Cooled
Output DC Voltage	28.9V Max.
Plug	Cannon/XLR
Operating Temperature	0°C - 40°C
Operating Humidity	20% - 85%RH
Dimensions	190 (L) x 145 (W) x 70mm (H)
Weight	0.0406kg

Specifications subject to change without notice.