

# VALEN BATTERY CHARGER

## BC VCC2408

- The Valen 24V 8A Convection Cooled Charger boasts superior quality and reliability, with the ability to correctly charge and maintain mobility batteries ensuring longevity.
- The Valen 24V 8A has an input voltage of 110V to 240V, allowing it to operate universally.
- Thermal protection against overheating is built-in, as well as reverse polarity, output shorting and spark protection.





# BC VCC2408

## BATTERY CHARGER

## SPECIFICATIONS

### Innovative Features

- Convection Cooling = no fan, no noise!
- Handle on the charger ensures it's easily portable
- Canon/XLR plug for mobility scooters and power wheelchair applications

### LED Indication

- Yellow on: Battery charging capacity
- Green on: Fully charged
- Orange Flash: Charger self-test fail
- Orange on: Charger not connected to the battery
- Orange & Yellow on: Normal charging
- Red Flash: Battery connected in the wrong polarity
- Red on: Low battery voltage/Wrong Battery

### Specifications

<b>Input Voltage</b>	100 - 240VAC
<b>Output Current</b>	8A
<b>Cooling</b>	Convection Cooled
<b>Output DC Voltage</b>	28.9V Max.
<b>Plug</b>	Cannon/XLR
<b>Operating Temperature</b>	0°C - 40°C
<b>Operating Humidity</b>	20% - 85%RH
<b>Dimensions</b>	190 (L) x 145 (W) x 70mm (H)
<b>Weight</b>	0.0406kg

Specifications subject to change without notice.