

EPS BATTERY CHARGER

24V 35A

BC31017

- Microprocessor controlled for optimized charging for different types of batteries
- 9 user-selectable charge profiles
- Short circuit and reverse polarity protection
- Power Factor
 Correction
- Battery monitor no overcharge possible
- Ah counter
- Battery temperature compensation
- Sealed housing
- Automatic shutoff
- Overheat protection
- PC interface
- Spark suppression







BC31017 BATTERY CHARGER SPECIFICATIONS



9 USER SELECTABLE CHARGE PROFILES

- Gel battery 50...90Ah
- Gel battery 100...600Ah
- Liquid lead battery 50...90Ah
- Liquid lead battery 100...400Ah
- Optima battery
- Genesis battery up to 60Ah
- Trojan battery 70...160Ah
- PzS battery Wet, 90Ah
- Calcium battery 70...150Ah

Specifications

Dimensions	340 x 190 x 75mm
Material	Casing material Aluminium
Weight	4.3kg
Battery nominal voltage	24V
Progr. output cur- rent	0.334A
Progr. output voltage	2033∨
Max. continuous output power	1000W
Input voltage	100240V
Input frequency	50/60Hz

Specifications subject to change without notice.









AUSTRALIA 1300 734 253 www.valen.com.au

NEW ZEALAND 0800 734 253 www.valen.co.nz