

VALEN BATTERY CHARGER

24V 8A

BC300006

- The Valen 24V 8A Convection Cooled Charger boasts superior quality and reliability, with the ability to correctly charge and maintain mobility batteries ensuring longevity.
- The Valen 24V 8A has an input voltage of 110V to 240V, allowing it to operate universally.
- Thermal protection against overheating is built-in, as well as reverse polarity, output shorting and spark protection.





BC30006

BATTERY CHARGER

SPECIFICATIONS

Innovative Features

- Convection Cooling = no fan, no noise!
- Handle on the charger ensures it's easily portable
- Canon/XLR plug for mobility scooters and power wheelchair applications

LED Indication

- Yellow on: Battery charging capacity
- Green on: Fully charged
- Orange Flash: Charger self-test fail
- Orange on: Charger not connected to the battery
- Orange & Yellow on: Normal charging
- Red Flash: Battery connected in the wrong polarity
- Red on: Low battery voltage/Wrong Battery

Specifications

Input Voltage	100 - 240VAC
Output Current	8A
Cooling	Convection Cooled
Output DC Voltage	28.9V Max.
Plug	Cannon/XLR
Operating Temperature	0°C - 40°C
Operating Humidity	20% - 85%RH
Dimensions	190 (L) x 145 (W) x 70mm (H)
Weight	0.0406kg

Specifications subject to change without notice.



QUALITY CERTIFIED
ISO 9001 : 2015



ENVIRONMENT CERTIFIED
ISO 14001 : 2015



SAFETY CERTIFIED
ISO 45001 : 2018

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz