ENLiFEN 12V 40Ah

12EL04033

- Valen ENLiFEN range features a Lithium Phosphate (LiFe PO4) battery constructed utilising individual 3.2V3200mAh cells in series and parallel.
- Superior life with an expectancy of 6 to 10 times more than standard AGM batteries.
- Up to two thirds lighter in weight than standard AGM batteries.
- Safer battery option as the customised built-in Valen ENLiFEN BMS prevents short circuit, over-voltage and over-discharge, as well as thermal runaway.
- Customisation allows the Valen ENLiFEN to be fitted into areas standard VRLA batteries cannot be utilised due to size restrictions.
- Maintenance-free battery range dramatically reduces the time spent on site for battery-related issues

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz

VALEN Power

12EL04033

BATTERY SPECIFICATIONS

Dimensions



Specifications

Nominals Voltage	12 Volt nominal
Capacity	40Ah
BMS	Internal
Chemistry	Lithium Iron Phosphate (LiFEPO4)
Dimensions	194 (L) x 132 (W) x 173(H)
Weight	5.15 kg
Terminal	M6
Container/Cover	ABS
Internal Resistance	≤40mΩ
Cycle Life	The cycle life is not less than 4000, the capacity retention rate is ≥ 80%.
Passive Protection Function	Over charge protection, over discharge protection, temperature protection, balanced function
Charge Voltage	14.4V ± 0.15V
Charge Current	≤20 ah
Continuous Discharge Current	20Ah
Peak Discharge Current	40A
Discharge Cut-off Voltage	10V
Charge Temperature	0°C to +45°C
Discharge Temperature	-20°C to +60°C
Storage Temperature	-20°C to +40°C

Specifications subject to change without notice.

ENLiFEN 12V 40Ah

Different Rate Discharge Curve(25℃)



Different Temperature Discharge Curve (0.5C)



State of Charge Curve (0.5C, 25℃)



Charging Characteristics (0.5C,25℃)



Different DOD Discharge Cycle Life Curve



Different Temperature Self Discharge Curve



Disclaimer:
While Valen have taken every effort to represent the ENLiFEN PO4 accurately within this specification, Valen advise the user to ascertain their own measurements and test the parameters and specifications to which the battery must conform. The Lithium battery technology is rapidly being developed and research is continually carried out to ensure that the ENLiFEN PO4 battery will meet the needs of a growing market.

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz