ENLiFEN 12V100Ah

12EL100070

- Valen ENLiFEN range features a Lithium Phosphate (LiFe PO4) battery constructed utilising individual 3.2V3200mAh cells in series and parallel.
- Superior life with an expectancy of 6 to 10 times more than standard AGM batteries.
- Up to two thirds lighter in weight than standard AGM batteries.
- Safer battery option as the customised built-in Valen ENLiFEN BMS prevents short circuit, over-voltage and over-discharge, as well as thermal runaway.
- Customisation allows the Valen ENLiFEN to be fitted into areas standard VRLA batteries cannot be utilised due to size restrictions.
- Maintenance-free battery range dramatically reduces the time spent on site for battery-related issues

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz

VALEN Power

12EL100070

BATTERY SPECIFICATIONS

Dimensions



Specifications

Nominals Voltage	12 Volt nominal
Capacity	100Ah
BMS	Internal
Chemistry	Lithium Iron Phosphate (LiFEPO4)
Dimensions	268(L) x 168(W) x 216(H)
Weight	13kg
Terminal	M8
Container/Cover	ABS
Internal Resistance	
Cycle Life	4000 at 80% DOD
Passive Protection Function	Over charge protection, over discharge protection, balanced function
Charge Voltage	14.4V ± 0.15V
Charge Mode	0.2C to 14.4 V, then 14.4V,charge current to 0.01C
Charge Current	≤50A
Continuous Discharge Current	50A
Peak discharge Current	100A
Discharge Cut-off Voltage	10V
Charge Temperature	0°C to +45°C
Discharge Temperature	-20°C to +60°C
Storage Temperature	-20°C to +40°C

Specifications subject to change without notice.

ENLiFEN 12V 100Ah

Different Rate Discharge Curve(25℃)



Different Temperature Discharge Curve (0.5C)



State of Charge Curve (0.5C, 25℃)



Charging Characteristics (0.5C,25℃)



Different DOD Discharge Cycle Life Curve



Different Temperature Self Discharge Curve



Disclaimer:
While Valen have taken every effort to represent the ENLiFEN PO4 accurately within this specification, Valen advise the user to ascertain their own measurements and test the parameters and specifications to which the battery must conform. The Lithium battery technology is rapidly being developed and research is continually carried out to ensure that the ENLiFEN PO4 battery will meet the needs of a growing market.

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz