ENDURO 2000VA ON-LINE UPS

PS80059

The Enduro series is a versatile Pure Sinewave, Online - Double Conversion UPS.
Its run time can be adjusted using one or more EBMs (extended battery modules), allowing for longer runtimes on a wide range of loads.

The Enduro Series is designed as a general-purpose UPS, most suitable for:

- Home and office workstations
- CCTV
- Modems & NBN
- Telecommunications
- Point of sale

If you need assistance in determining the run time or any other questions, please reach out to the team today.

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz

PS80059

UPS SPECIFICATIONS

Specifications

Capacity	2000/1800W
Input	
Voltage Range	230V +/- 20%
Frequency Range	45Hz - 65Hz
Output	
Voltage Regulation	230VAC+/-2%
Frequency	50 Hz ± 0.1Hz
Waveform	Pure Sinewave
Battery	
Type	Sealed lead acid, maintenance free
Configuration	6 x 12V/9AH
Charge current(Max)	12A
Recharge	5 hours to 90% capacity after complete discharge
Comms & Management	
Software	Windows 95/98/NT/2000/XP/Vista/7, Windows Server 2003/2008 Linux Debian, Redhat, Fedora, Suse, Ubuntu, CentOS, Novell, Mac, FreeBSD
Ports	USB and RS-232 standard
Optional	SNMP & relay (trigger voltage free contacts)
LED/LCD display	Load, battery, input, output, operating
Audible alarm	Battery mode, low battery, overload, fault
Protection	
Surge protection	2200 Joules / 60,000 Amps
Input protection	Compliance with IEEE 587
Short circuit	Resettable circuit breaker
EPO	Shuts down UPS immediately
EMC	EN50091-2, C Tick/RCM
Network	RJ45, fulltime network protection
Physical	
Temperature	0 - 40 °C
Humidity	0 - 95% (non-condensing)
Noise level	<50dB at 1m
Dimensions	440x600x86.5
Weight	26.3kg

Features

- On-line double conversion
- Rack and tower mount
- Output power factor 0.9, input power factor 0.99
- Longer run time through EBM
- Interactive LCD screen
- Smart management and control software
- Emergency power off function (EPO)
- Generator compatible

Rear Panel

1. Intelligent slot (SNMP card, dry contact etc.)
2. USB port
3. RS-232 port
4. Input breaker
5. RJ45 surge protection
6. EPO

Runtime in Minutes

Load VA/W	200VA 180W	400VA 360W	600VA 540W	800VA 720W	1000VA 900W	1200VA 1080W	1500VA 1350W	2000VA 1800W
Enduro 2000	118	58	38	24	20	16	12	7

Specifications subject to change without notice.

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz