# FIELD CABINET, DOUBLE DOOR, 1600 X 900 X 2037

## BE73050

- Valen's plinth-mounted Field Cabinets are designed for heavy-duty outdoor use, protecting sensitive data, network, and electrical equipment.
- Durable Construction: Made from 2.0mm galvanised steel with rain hood, sunshield, plinth, lifting eye bolts, and 3.0mm gland plate.
- High Protection Ratings: IP66, IK10, NEMA 4 (IP65 for fan/filter cutouts); meets IEC62208, IEC/EN/AS60529, and IEA-310-D standards
- Ventilation Ready: Includes four 125mm x 125mm cutouts with removable vent hoods for optional fans and filters (sold separately).
- Secure Design: Flush-mounted doors with concealed hinges, 110° opening, and heavy-duty door stays for anti-vandal performance.

AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz

# BE73050

## ENCLOSURE SPECIFICATIONS

## Dimensions

1600 (W) x 900 (L) x 2037 (H)mm

## Specifications

**Protection**
Complies with IP66, IK10, and NEMA 4 (IP65 at fan/filter cutouts), meeting IEC62208, IEC/EN/AS60529, and IEA-310-D standards.

**Cabinet Body**
Robust mono-block design using 2.0mm galvanised steel, with rain hood, sun shield, plinth, vent hoods, and 4 lifting eye bolts. Includes flat sealing surfaces for extended gasket life and a 3.0mm steel split gland plate at the base. Four 125mm x 125mm fan/filter cut-outs with removable vent hoods (fans/filters sold separately). Precision automated fabrication ensures consistency.

**Doors**
Front and rear doors are 2.0mm galvanised steel, flush-mounted for anti-vandal protection. Concealed hinges with captive pins allow 110° opening; fitted with heavy-duty door stays.

## DOUBLE DOOR FIELD CABINET

**Rack Rails**
Supplied with front and rear 19" data rack rails, made from 1.5mm galvanised steel.

**Seals**
Durable full-perimeter FIP polyurethane door seals for long-term protection.

**Locks**
Each door includes a 3-point locking system with key-lock swing handle. Alternate lock options available on request.

**Gland Plate**
3.0mm aluminium split gland plates integrated into the base for cable entry.

**Finish**
Smooth epoxy-polyester powder coat (UL approved), 80–120µm thick.

**Colour**
Standard colour is T33 Smoke Blue; other colour options available on request.

Specifications subject to change without notice.



AUSTRALIA
1300 734 253
sales@valen.com.au
www.valen.com.au

NEW ZEALAND
0800 734 253
sales@valen.co.nz
www.valen.co.nz